

Application No. N/A

25. (Amended) Switch according to claim 1 characterised in that the switch has in addition to the switch elements (21, 21', 22, 22', 23, 24, 24') also further electrical and/or electronic structural elements.

26. (Amended) Switch according to claim 1 characterised in that the zone (11) of the haptic element (1, 1', 1'') associated with the switch elements (21, 21', 22, 22', 23, 24, 24') forms at the same time at least one operating element of the haptic element (1, 1', 1'').

### REMARKS

Claims 1-26 remain in the application. Claims 3, 6-8, 10-12, and 17-26 have been amended. It is respectfully requested that the foregoing preliminary amendment be entered prior to examination.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "Version with markings to show changes made."

Respectfully submitted,

CHRISTIE, PARKER & HALE, LLP

By D. Bruce Prout #31,953

For D. Bruce Prout  
Reg. No. 20,958  
626/795-9900

DBP/aam

200601.0200

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

3. (Amended) Switch according to claim 1 [~~or 2~~] characterised in that the haptic element (1, 1', 1'') has no electrically conductive component parts which can be coupled electrically with the switch elements (21, 21', 22, 22', 23, 24, 24').
6. (Amended) Switch according to claim 1, [~~4 or 5~~] characterised in that the haptic element (1, 1', 1'') has no electrical structural elements apart from an electrical conductor.
7. (Amended) Switch according to claim 1, [~~4, 5 or 6~~] characterised in that the haptic element (1, 1', 1'') has as a single electrically conductive component which can be coupled electrically with the switch elements (21, 21', 22, 22', 23, 24, 24') a contact bridge with which an electrical connection can be established between two switch elements (21, 21', 22, 22', 23, 24, 24').
8. (Amended) Switch according to [~~one of the preceding claims~~] claim 1, characterised in that the relevant zones (11, 20, 20') of the conductor (2, 2a, 2b) and the haptic element (1) are formed as mechanical plug connectors wherein a base body (10) of the haptic element (1) has a socket zone (12) with which the zone (20, 20') of the flexible conductor (2) supporting the switch elements (21, 21', 22, 22') can be brought into positive engagement.
10. (Amended) Switch according to [~~claims 8 and 9~~] claim 9 characterised in that the mechanical reinforcement is formed as a frame (124) around the edges, a plate (123, 125) at the back or a cast element (121, 122) which surrounds the relevant zone (20).
11. (Amended) Switch according to [~~one of the preceding claims~~] claim 9 characterised in that the mechanical reinforcement has at least one detent element (125b) for securing the insert position in respect of the haptic element and/or means (125a) for sealing the plug zone against damp.
12. (Amended) Switch according to [~~one of claims 1 to 7~~] claim 1 characterised in that the relevant zones (11, 20') of the conductor (2) and haptic element (1', 1'') are formed as clamp-fit

**Application No. N/A**

connections wherein a base body (10) of the haptic element (1', 1'') has a socket zone (120) and a fixing element (12', 12'') connectable therewith so that the zone (20') of the flexible conductor (2) supporting the switch elements (22, 22') can be clamped between the socket zone (120) of the haptic element and the fixing element (12', 12'').

17. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch elements (22, 22') provided on the flexible conductor (2) are formed as electrical contact faces which are allocated an electrical contact bridge which is connected to an operating element (11) of the haptic element (1) and which when the operating element (11) is actuated closes the electrical circuit.

18. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch elements (24, 24') provided on the flexible conductor (2) are provided in boxes, e.g. in the form of SMD switches or switch mats.

19. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch elements provided on the flexible conductor (2) are designed as magneto-resistive structural elements (e.g. Hall elements) which are each allocated a permanent magnet which is connected to an actuating element of the haptic element.

20. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch elements provided on the flexible conductor (2) are formed as inductive or capacitive close range approach switches.

21. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1, characterised in that the switch elements provided on the flexible conductor (2) are formed as transponder readers.

22. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch elements provided on the flexible conductor (2) are formed as passive or active optical elements allocated on the part of the operating elements of the haptic element means for

10069201-022002

Application No. N/A

reflection for the purpose of establishing a visual transmission path or means for interrupting a visual transmission path.

23. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that further structural elements (3a, 3b) such as for example an optical element for illuminating the switch, a micro controller, resistances, diodes or the like, are mounted on the zone (20) of the flexible conductor (2) supporting the switch elements.

24. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the zone (20) supporting the switch elements is detachably connected to the haptic element (1, 1', 1'').

25. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the switch has in addition to the switch elements (21, 21', 22, 22', 23, 24, 24') also further electrical and/or electronic structural elements.

26. (Amended) Switch according to ~~[one of the preceding claims]~~ claim 1 characterised in that the zone (11) of the haptic element (1, 1', 1'') associated with the switch elements (21, 21', 22, 22', 23, 24, 24') forms at the same time at least one operating element of the haptic element (1, 1', 1'').